



**Main**

Range of product	Thorsman
Product or component type	Hammer fixing
Product name	Thorsman THI
Device short name	THI
Provided equipment	Screw
Device application	High load installation in board material

**Complementary**

Colour tint	Transparent
Practical load capacity	500 N pull-out load concrete B25 400 N pull-out load brick 300 N pull-out load sandstone
Practical load capacity	50 kg pull-out load concrete B25 40 kg pull-out load brick 30 kg pull-out load sandstone
Ambient air temperature for operation	-40...70 °C
Diameter	6 mm
Length	50 mm

**Environment**

quantity per set	Set of 100
sale per indivisible quantity	100

**Offer Sustainability**

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0748 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.