

230DRAVL

Resimax Meterbox 21 module with service fuse lock -
H680 x W470 x D280 mm



Main

Range	Resi MAX
Product or component type	Meter box
Enclosure/cubicle description	Plain door enclosure
Device application	Distribution Metering
Targeted country	Victoria

Complementary

Enclosure mounting	Surface Semi flush
Number of modules	21
Provided equipment	Fuse links Enclosure DIN rail Removable meter panel Neutral link Fascia plate
Function available	Cable protection slide Fuse protection lock
Protection device type	Miniature circuit breaker (MCB) 1P <= 63 A 6 kA
Cable entry	Knock-out at top and bottom Knock-out at rear
Door type	Ventilated and manually removable door with door retainer
Door opening side	Right
Lock type	Padlockable
Material	Galvanised iron
Protective treatment	Epoxy powder coat
Width	470 mm
Height	680 mm
Depth	280 mm
Colour	Beige

Environment

IP degree of protection	IP23
standards	AS/NZS 3000

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.