



## Main

|                               |                       |
|-------------------------------|-----------------------|
| Range                         | Clipsal Iconic        |
| Product or component type     | Switched socket       |
| Device presentation           | Complete product      |
| Outlet poles configuration    | 2P + E with shutter   |
| Type of packing               | Polybag               |
| Quantity per set              | Set of 10             |
| Sale per indivisible quantity | 1                     |
| Rated current                 | 10 A, 250 V AC, 50 Hz |

## Complementary

|                                       |   |
|---------------------------------------|---|
| Device mounting                       | Flush   |
| Number of power socket outlets        | 2   |
| Number of rocker                      | 3   |
| Outlet standard                       | Australian  |
| Outlet standard description           | With earthing contact   |
| Outlet standard                       | Australian/New Zealand  |
| Ground lug position                   | Straight 180° position  |
| Fixing mode                           | By screw  |
| Installation direction                | Horizontal  |
| Colour tint                           | Vivid white (VW)  |
| Surface finish                        | Matt  |
| Ambient air temperature for storage   | 0...60 °C   |
| Ambient air temperature for operation | 0...45 °C   |
| Relative humidity                     | 10...95 %   |
| Electrical durability                 | 12000 cycles  |
| Screwdriver shape                     | Philips No 2<br>Square drive no 1 (SQ1)   |
| Clamping connection capacity          | 1 x 2.5...4 x 2.5 mm <sup>2</sup> (rigid)<br>1 x 2.5...4 x 2.5 mm <sup>2</sup> (rigid)<br>1 x 2.5...4 x 2.5 mm <sup>2</sup> (stranded)<br>1 x 2.5...4 x 2.5 mm <sup>2</sup> (flexible)  |
| Wire stripping length                 | 16 mm   |
| Material                              | ABS (acrylonitrile butadiene-styrene) for cover frame<br>POM (polyoxymethylene) for shutter<br>POM (polyoxymethylene) for shutter<br>POM (polyoxymethylene) for locking bar<br>PC (polycarbonate) for fixing frame<br>PP (polypropylene) for rocker<br>PC (polycarbonate) for cover frame |
| Height                                | 120 mm  |
| Width                                 | 78 mm   |
| Depth                                 | 35 mm   |
| Product weight                        | 0.092 kg  |
| Standards                             | AS/NZS 3112<br>AS/NZS 3133<br>AS/NZS 60669.1  |

## Environment

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1817 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations                                 |