



Main

Product brand	Clipsal
Range of product	Series 4

Complementary

Curve code	D
Number of poles	1
[In] rated current	6 A
Number of modules	1
[Ue] rated operational voltage	240 V
Breaking capacity	10 kA conforming to EN 60898
Network type	AC
Network frequency	50/60 Hz
IP degree of protection	IP20 IEC 60529 IP40 modular enclosure IEC 60529

Environment

ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...70 °C
standards	AS/NZS 60898
tropicalisation	2
relative humidity	95 % 55 °C
height	81 mm
width	18 mm
depth	78.5 mm
product weight	115 g
mechanical durability	20000 cycles
electrical durability	20000 cycles
connections - terminals	Screw terminal 0.75...16 mm ² rigid 1 Screw terminal 0.33...10 mm ² flexible 1 Screw terminal 0.33...10 mm ² flexible with ferrule 1
wire stripping length	13 mm
tightening torque	2 N.m

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations