



### Main

Product brand	Clipsal
Range of product	Series 4

### Complementary

Curve code	D
Number of poles	1
[In] rated current	25 A
Number of modules	1
[Ue] rated operational voltage	240 V
Breaking capacity	10 kA conforming to EN 60898
Network type	AC
Network frequency	50/60 Hz
[Ui] rated insulation voltage	500 V
IP degree of protection	IP20 IEC 60529 IP40 modular enclosure IEC 60529

### Environment

ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...70 °C
standards	AS/NZS 60898
tropicalisation	2
relative humidity	95 % 55 °C
height	81 mm
width	18 mm
depth	78.5 mm
product weight	115 g
mechanical durability	20000 cycles
electrical durability	10000 cycles
connections - terminals	Screw terminal 0.75...16 mm <sup>2</sup> rigid 1 Screw terminal 0.33...10 mm <sup>2</sup> flexible 1 Screw terminal 0.33...10 mm <sup>2</sup> flexible with ferrule 1
wire stripping length	13 mm
tightening torque	2 N.m

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.