

4CBEM2T

PowerTag Wiser Energy Monoconnect 1P+N Top position Max 63A Energy Sensor



Main

Range	Wiser
Product name	PowerTag Wiser M63
Product or component type	Energy sensor
Product brand	Clipsal
Poles description	1P + N
Max current	63 A
[I _b] basic current	10 A
Starting current	40 mA
Saturation current	130 A
Product specific application	Overload alarm Circuit monitoring Load monitoring Energy production monitoring (photovoltaic)
Concentrator compatibility	Wiser IP module
Range compatibility	Resi MAX & MAX4
Accuracy class	Class 1 current IEC 61557-12 Class 0.5 voltage IEC 61557-12 Class 1 active energy IEC 61557-12
Mounting location	Top
Mounting support	On circuit breaker
Fixing mode	Screwed in terminals
Product destination	Switchboard
Type of measurement	Active energy Current Voltage
Event management	Voltage loss with measured current at voltage loss
Communication mode	Radio frequency 2.4...2.4835 GHz IEEE 802.15.4

Complementary

Electrical connection	Connector tooth
Cable cross section	1 rigid cable 1.5...16 mm ² 2 stranded cable 1.5...2.5 mm ² 2 rigid cable 1.5...2.5 mm ² 1 stranded cable 1.5...16 mm ²
[U _s] rated supply voltage	230 V AC +/- 20 %
Network frequency	50/60 Hz
Power consumption in VA	<= 2 VA
IP degree of protection	IP20 according to IEC 60529
Height	16.5 mm
Width	35.4 mm
Depth	42.7 mm
Product weight	17.5 g
Colour	White RAL 9003

Environment

operating altitude	0...2000 m
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C
overvoltage category	III according to IEC 61010-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

measurement category	Category III according to IEC 61010-2-30
IK degree of protection	IK05
pollution degree	3
relative humidity	0...95 % (in operation) at 45 °C according to IEC 60721-3-3
vibration resistance	3M4 according to IEC 60721-3-3
environmental characteristic	Dustproof: class 3S3 according to IEC 60721-3-3 Salt mist: class 3C2 according to IEC 60721-3-3

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1802 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold