



## Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket
Device application	Power supply
Colour	Orange RAL 2004

## Complementary

Plug, socket category	Low voltage
Plug, socket, control station shape	Straight
Mounting mode	External mounting
[In] rated current	50 A
[Ue] rated operational voltage	500 V AC @ 50 Hz EN 60309-2
Poles description	3P + N + E
Voltage colour	Black
Duration	7 h
Material	Polycarbonate for the housing
Contacts material	Brass for the sleeves
Connections - terminals	Screw terminals 2.5...25 mm <sup>2</sup>
Connections - terminals	Screw terminal
Socket number	1
Socket-outlet type	U
Outlet standard	Industrial
Cable outer diameter	9...29 mm
Cable entry	Cable gland
Thread type	M40
Product weight	0.409 kg
Depth	180 mm
Length	184 mm
Width	90 mm
Height	90 mm
Targeted country	Australia

## Environment

IP degree of protection	IP66 conforming to AS 60529
ambient air temperature for operation	-25...75 °C
standards	AS/NZS 3120

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0802 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations