



## Main

|                           |            |
|---------------------------|------------|
| Range of product          | Series 56  |
| Product or component type | Switch     |
| Colour                    | Grey cover |

## Complementary

|                              |   |
|------------------------------|---|
| Colour code                  | GY  |
| Motor starter type           | Direct on line  |
| Control type                 | Push-button   |
| [Us] rated supply voltage    | 415 V AC 50 Hz  |
| Network type                 | AC  |
| Rated operational power in W | 7.5 kW 415 V AC-3   |
| Connections - terminals      | Screw terminal cable stiffness solid<br>Screw terminal cable stiffness stranded |
| Tightening torque            | 0.8 N.m   |
| Height                       | 204 mm  |
| Width                        | 101 mm  |
| Product weight               | 1.327 kg  |
| Targeted country             | Australia   |
| Market segment               | Small commercial<br>Industry<br>Utility   |

## Environment

|                                       |                             |
|---------------------------------------|-----------------------------|
| suitability for isolation             | No                          |
| IP degree of protection               | IP66 conforming to AS 60529 |
| ambient air temperature for operation | -25...75 °C                 |
| standards                             | AS/NZS 3133<br>AS/NZS 3100  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1650 - Schneider Electric declaration of conformity |
| REACH                            | Reference contains SVHC above the threshold                           |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations                                 |