



Main

Range of product	Series 56
Product or component type	Switch
Colour	Grey cover

Complementary

Colour code	GY
Motor starter type	Direct on line
Control type	Push-button
[Us] rated supply voltage	240 V AC 50 Hz
Network type	AC
Rated operational power in W	4 kW 240 V AC-3
[Ie] rated operational current	9 A
Overload current	1...1.6 A
Connections - terminals	Screw terminal cable stiffness solid Screw terminal cable stiffness stranded
Tightening torque	0.8 N.m
Network number of phases	3 phases
Product destination	Push-button 2
Height	294 mm
Width	101 mm
Product weight	4.98 kg
Targeted country	Australia
Market segment	Small commercial Industry Utility

Environment

suitability for isolation	No
IP degree of protection	IP66 conforming to AS 60529
ambient air temperature for operation	-25...75 °C
standards	AS/NZS 3133 AS/NZS 3100

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1650 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.