


56E8-GY

56 Series Enclosure - 8 Gang - 2 x 25mm - 2 x 32mm conduit entries



Main

| | |
|------------------|---------------------|
| Range of product | Series 56 |
| Range | Clipsal - 56 Series |
| Product brand | Clipsal |
| Colour | Grey RAL 7035 |

Complementary

| | |
|--------------------------|---|
| Number of gangs | 8 gangs |
| Device mounting | Surface |
| Mounting mode | Wall-mounted |
| Cable entry number | 4 |
| Material | PVC (polyvinyl chloride) for the housing |
| Number of mounting holes | 28 |
| Cable entry | 2 x 32 mm cut-out 2 x 40 mm cut-out 4 x 25 mm cut-out |
| Length | 63 mm |
| Width | 198 mm |
| Depth | 63 mm |
| Height | 396 mm |
| Product weight | 1.17 kg |
| IP degree of protection | IP66 conforming to AS 60529 |
| Standards | AS 3100 |

Environment

| | |
|---------------------------------------|-------------|
| ambient air temperature for operation | -25...75 °C |
|---------------------------------------|-------------|

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1501 - Schneider Electric declaration of conformity |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.