

## 56K1CV310-GY

56 Series Switched Socket Outlet -Key Lock -10A -3  
Pin -1 Pole Switch -250V -Grey



### Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Switched socket
Device application	Power supply
Colour	Grey
Outlet standard	Australian/New Zealand

### Complementary

Plug, socket category	Low voltage
Plug, socket, control station shape	Angled Straight
Mounting mode	Surface mounting
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC @ 50 Hz EN 60309-2
Poles description	1P + N + E
Voltage colour	Blue
Protection type	Without protection
Duration	6 h
Material	Polycarbonate for the cover
Contacts material	Phosphor bronze for the pins
Connections - terminals	Screw terminals 1.5...6 mm <sup>2</sup>
Depth	85 mm
Width	101 mm
Height	204 mm
Targeted country	Australia

### Environment

IP degree of protection	IP66 conforming to AS 60529
ambient air temperature for operation	-25...75 °C
standards	AS/NZS 3112 AS/NZS 4417.1

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1501 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.