



Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Switch
Device presentation	Basic element with full cover plate
Device application	Control
Colour	Grey for cover
Handle colour	Grey
Suitability for isolation	Yes

Complementary

Switch function	2-pole
Poles description	2P
Control type	Rotary knob
Number of poles	2
Device mounting	Surface
Fixing mode	By screws
Connections - terminals	Screw terminal 4...16 mm ² cable stiffness solid
Material	PC (polycarbonate)
Tightening torque	0.8 N.m
Local signalling	Without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	32 A
Breaking capacity	32 kA
Motor M-rating AS3133	M180 at 250 V
Rotary handle padlocking	2 padlocks of 8 mm diameter
Marking	ON-OFF
Marking location	Marking on surface
Height	107 mm
Width	101 mm
Depth	108 mm
Product weight	0.68 kg
Targeted country	Australia

Environment

ambient air temperature for operation	-25...75 °C
IP degree of protection	IP66 conforming to AS 60529
standards	AS/NZS 3133

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1650 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations