

CAD32FD

TeSys D control relay - 3 NO + 2 NC - ≤ 690 V -
110 V DC standard coil



Main

| | |
|---------------------------|-----------------|
| Range | TeSys |
| Product name | TeSys CAD |
| Product or component type | Control relay |
| Device short name | CAD |
| Contactors application | Control circuit |

Complementary

| | |
|---|--|
| Utilisation category | AC-14 AC-15 DC-13 |
| Pole contact composition | 3 NO + 2 NC |
| [Ue] rated operational voltage | ≤ 690 V AC 25...400 Hz |
| Control circuit type | DC standard |
| [Uc] control circuit voltage | 110 V DC |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947 |
| [Ith] conventional free air thermal current | 10 A at ≤ 60 °C |
| Irms rated making capacity | 140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1 |
| [Icw] rated short-time withstand current | 100 A 1 s 120 A 500 ms 140 A 100 ms |
| Associated fuse rating | 10 A gG conforming to IEC 60947-5-1 |
| [Ui] rated insulation voltage | 690 V conforming to IEC 60947-5-1 600 V certifications UL 600 V certifications CSA |
| Mounting support | Plate Rail |
| Connections - terminals | Screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end Screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end |
| Tightening torque | 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm |
| Control circuit voltage limits | 0.1...0.25 Uc drop-out 0.7...1.25 Uc operational |
| Operating time | 15...25 ms coil de-energisation and NC closing 53...72 ms coil energisation and NO closing 16...24 ms coil de-energisation and NO opening 47...63 ms coil energisation and NC opening |
| Mechanical durability | 30 Mcycles |
| Operating rate | 180 cyc/mn |
| Time constant | 28 ms |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|--------------------------------|--|
| Inrush power in W | 5.4 W at 20 °C |
| Hold-in power consumption in W | 5.4 W at 20 °C |
| Minimum switching voltage | 17 V |
| Minimum switching current | 5 mA |
| Non-overlap time | 1.5 ms on de-energisation (between NC and NO contact) 1.5 ms on energisation (between NC and NO contact) |
| Insulation resistance | > 10 MOhm |
| Mechanical robustness | Shocks control relay open 10 Gn for 11 ms IEC 60068-2-27 Shocks control relay closed 15 Gn for 11 ms IEC 60068-2-27 Vibrations control relay open 2 Gn, 5...300 Hz IEC 60068-2-6 Vibrations control relay closed 4 Gn, 5...300 Hz IEC 60068-2-6 |
| Height | 77 mm |
| Width | 45 mm |
| Depth | 93 mm |
| Product weight | 0.58 kg |

Environment

| | |
|---------------------------------------|---|
| standards | VDE 0660 IEC 60947-5-1 NF C 63-140 BS 4794 EN 60947-5 |
| product certifications | CSA UL |
| IP degree of protection | IP2x front face conforming to VDE 0106 |
| protective treatment | TH conforming to IEC 60068 |
| ambient air temperature for operation | -40...70 °C |
| ambient air temperature for storage | -60...80 °C |
| operating altitude | 3000 m without derating |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0627 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |