



## Main

Range of product	Canalis
Product or component type	Busbar trunking
Product compatibility	KBA

## Complementary

Device application	Lighting Power socket distribution
Radiated magnetic field	2 pT
[Ue] rated operational voltage	230...400 V
[Uimp] rated impulse withstand voltage	4 kV
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	25 A at 35 °C
Network frequency	50/60 Hz
[Icw] rated short-time withstand current	0.44 kA
[Ipk] rated peak withstand current	4.4 kA
Thermal stress limit	195 kA <sup>2</sup> .s
THDI	25 A at 0...15 % 20 A at 15...33 % 16 A at 33...100 %
Voltage drop	0.72 V with power factor = 1 at 50 Hz with 1A for 100 m long 0.67 V with power factor = 0.9 at 50 Hz with 1A for 100 m long 0.61 V with power factor = 0.8 at 50 Hz with 1A for 100 m long 0.54 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By clips
Busbar description	Straight length
Busbar trunking polarity	L + N + PE
Number of tap-off outlets	5
Control type	Without
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	3140 mm
Depth	30 mm
Height	46 mm
Length	3 m
Product weight	2.4 kg
Quantity per set	Set of 6

## Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
IK degree of protection	IK06 conforming to EN/IEC 62262
ambient air temperature for operation	0...35 °C at 100 % of In 35...40 °C at 96 % of In

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

40...45 °C at 93 % of In  
45...50 °C at 89 % of In  
50...55 °C at 85 % of In

---

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations