



Main

| | |
|------------------------------|---|
| Range | TeSys |
| Device short name | LA1SK |
| Product or component type | Auxiliary contact block |
| Product compatibility | LC1SK |
| Auxiliary contacts operation | Instantaneous |
| Pole contact composition | 2 NO |
| Connections - terminals | Screw clamp terminals 2 cable 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 1.5...6 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 0.5...6 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.35...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.35...6 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.35...1.5 mm ² - cable stiffness: flexible - without cable end |

Complementary

| | |
|---|---|
| Mounting location | Front side |
| [Ui] rated insulation voltage | 690 V - conforming to BS 5424 690 V - conforming to IEC 60947 690 V - conforming to VDE 0110 group C 690 V - conforming to CSA C22.2 No 14 |
| [Ue] rated operational voltage | 690 V AC <= 400 Hz |
| [Ith] conventional free air thermal current | 10 A at <= 55 °C |
| Associated fuse rating | IEC 60947 VDE 0660 |
| Tightening torque | 0.8 N.m - on screw clamp terminals |
| Width | 27 mm |
| Product weight | 0.022 kg |

Environment

| | |
|---------------------------------------|---|
| standards | BS 5424 IEC 60947 NF C 63-110 VDE 0660 |
| product certifications | CSA UL |
| IP degree of protection | IP2x |
| protective treatment | TC conforming to IEC 60068 |
| ambient air temperature for operation | -20...50 °C |
| ambient air temperature for storage | -50...70 °C |
| operating altitude | 2000 m without derating in temperature |

Offer Sustainability

| | |
|-------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0718 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

